

# CA-134I Series

## 4-port RS-422/485 PC/104 modules with 2 KV isolation



The certification logos shown here apply to some or all of the products in this section. For details, see "Regulatory Approvals" under "Specifications" below.

- > 921.6 Kbps maximum baudrate for super fast data transmission
- > On-chip H/W and S/W flow control
- > Built-in 15 KV ESD protection
- > IRQ settings, I/O settings, and serial interface are jumper and DIP switch selectable
- > Onboard Tx and Rx LED indicators for each port
- > Windows CE 5.0/6.0 and Windows XP embedded operating systems supported
- > Wide temperature model available for -40 to 85°C environments



### Overview

The CA-134I PC/104 modules are reliable, high performance, multiport serial communication solutions that have 4 RS-422/485 ports, and can be used with PC/104 CPU boards that accept the PC/104 expansion

interface. Optional DB9 and DB25 connection cables are available for connecting to serial devices, and the CA-134I's versatile driver support makes the modules suitable for a wide range of applications.

### Specifications

#### Hardware

**Comm. Controller:** 16C550C or compatible x 4  
**Bus:** PC/104 bus  
**Connector:** 40-pin box header  
**DIP Switches:** I/O base address, interrupt vector, serial interface

#### Serial Interface

**Number of Ports:** 4  
**Serial Standards:** RS-422/485  
**Max. No. of Boards per PC:** 4

#### Serial Line Protection

**ESD Protection:** 15 KV on the board  
**Optical Isolation Protection:** 2 KV

#### Performance

**Baudrate:** 50 bps to 921.6 Kbps

#### Serial Communication Parameters

**Data Bits:** 5, 6, 7, 8  
**Stop Bits:** 1, 1.5, 2  
**Parity:** None, Even, Odd, Space, Mark  
**IRQ:** 3, 4, 5, 6, 7, 9, 10, 11, 12, 15 (shared for all ports)  
**FIFO:** 64 bytes

#### Serial Signals

**RS-422:** TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND  
**RS-485-4w:** TxD+(B), TxD-(A), RxD+(B), RxD-(A), GND  
**RS-485-2w:** Data+(B), Data-(A), GND

#### Driver Support

**Operating Systems:** Windows (2000/XP/2003/Vista), Windows 9X/ME/NT, Windows CE 5.0/6.0, Windows XP Embedded, DOS, Linux 2.4, Linux 2.6 (x86/x64), QNX 4/6

#### Physical Characteristics

**Dimensions:** 90 x 96 mm (3.54 x 3.78 in)

#### Environmental Limits

**Operating Temperature:**  
 Standard Models: 0 to 55°C (32 to 131°F)  
 Wide Temp. Models: -40 to 85°C (-40 to 185°F)  
**Operating Humidity:** 5 to 95% RH  
**Storage Temperature:** -40 to 55°C (-40 to 131°F)

#### Regulatory Approvals

**FCC:** Part 15 Class A  
**EMS:** EN55022, EN55024, EN61000-3-2, EN61000-3-3, IEC 61000-6-2, IEC 61000-6-4, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11 (DIPS)

#### Warranty

**Warranty Period:** 5 years  
**Details:** See [www.moxa.com/warranty](http://www.moxa.com/warranty)

### Ordering Information

#### Available Models

**CA-134I:** 4-port RS-422/485 PC/104 module with optical isolation, 0 to 55°C operating temperature  
**CA-134I-T:** 4-port RS-422/485 PC/104 module with optical isolation, -40 to 85°C operating temperature

#### Connection Options (can be purchased separately)

**CBL-F40M9x4-50:** 40-pin box header to DB9 male x 4 connection cable, 50 cm  
**CBL-F40M25x4-50:** 40-pin box header to DB25 male x 4 connection cable, 50 cm

#### Package Checklist

- CA-134I or CA-134I-T module
- Document and Software CD
- Quick Installation Guide (printed)
- Warranty Card